



hot wallet

Version 1.0.2

The DiscountCoin Core Team

February 2018

	3
DiscountCoin-qt	3
(private key) 가	3
Configuration	3
(collateral transaction)	4
	4
	5
	5
	5

:

- hot wallet
-
-

DiscountCoin-qt

DiscountCoin-qt.exe

Wallet

“Receive Tab”

가

“Receive Tab”

(private key) 가

“Help” -> “Debug Console”

(private key)

masternode genkey

Configuration

*C:/users/***Your windows username***/appdata(hidden)/roaming/DiscountCoin*

Configuration

(Configuration DiscountCoin.conf)

rpcuser=RandomStringOfYourChoice_with_no_spaces
rpcpassword=AnotherRandomStringOfYourChoice_with_no_spaces
rpccallowip=127.0.0.1
rpcport=9447
listen=1
server=1
daemon=1
port=9448
masternode=1
masternodeaddr=YourIP:9448
masternodeprivkey=YourPrivateKeyPreviouslyGenerated

Wallet

(collateral transaction)

(reward) 가 (collateral)
5000 DSC
20 (confirmations)

"Help" -> "Debug Console" "masternode start"

"Masternode started successfully"

가

가 PRE_ENABLE

ENABLED

(rewards)

(blocks)

가

DiscountCoin-qt.exe

- - C:\DiscountMN
- - C:\DiscountMN\MN1
 - C:\DiscountMN\MN2
 - C:\DiscountMN\MN3
 - C:\DiscountMN\MN4 ...
- DiscountCoin-qt.exe
 - Discount-MNx.exe (x = 1 to 4)
- "data" (C:\DiscountMN\MNx\data)
- - C:/users/***Your windows username***/appdata(hidden)/roaming/DiscountCoin*
- "blk0001.dat" "txleveldb" "data"
- Win+R , "cmd"
- (command shell)
- `echo start Discount-MN1.exe -datadir=./data > C:\DiscountMN\MN1\startmn1.cmd`
MN2, MN3, MN4
- `echo start Discount-MN2.exe -datadir=./data > C:\DiscountMN\MN2\startmn2.cmd`
- `echo start Discount-MN3.exe -datadir=./data > C:\DiscountMN\MN3\startmn3.cmd`
- `echo start Discount-MN4.exe -datadir=./data > C:\DiscountMN\MN4\startmn4.cmd`
- startmn1.cmd, startmn2.cmd, startmn3.cmd, startmn4.cmd
- Wallet

가

Wallet

가

Translated into Korean by Rain#1624 on Discord
If it helps and feels so good, My DiscountCoin address is :

DUFRN1jgm3w65nxBkQQ4snRfcbVKJUgcN2

가 : Rain#1624
...

DUFRN1jgm3w65nxBkQQ4snRfcbVKJUgcN2